

SAFETY INFORMATION

Please obey the basic safety instructions when you use our electric heated towel rail products.

READ THESE INSTRUCTIONS CAREFULLY. Keep them handy for future reference.

- This appliance is used for warming and drying towels, therefore it is hot to touch. Young children or infirm persons should be supervised when the product is working and ensure that they do not touch the appliance.
- The appliance will feel hotter to touch during warmer periods because of the rise in ambient temperature. Also the insulation effect of towels will cause the operating temperature to increase slightly.
- The appliance should be installed so that switches and other controls cannot be touched by a person in the bath or shower.
- This appliance is **ONLY** used for warming and drying towels, **DO NOT** use it for any other purpose.
- To avoid danger this product **MUST NOT** be used to carry towels or any other articles that have been in contact with oil, petroleum based products or dry cleaning fluids.
- Make sure the voltage complies with the specification on the rating label, or elsewhere in these instructions.
- **DO NOT** immerse in any liquid.
- **DO NOT** allow the power cord to contact with the hot surface when it is working.
- If the product does not work well or is damaged, it must be fixed or replaced by the manufacturer, its service agent or similarly qualified persons.
- **WARNING:** The bottom rail of this product **MUST** be installed at least 600mm above the floor in order to avoid risk of harm to young children.

INSTALLATION & ILLUSTRATION

Step 1: Mark mounting holes according to dimension of rails remembering to also allocate mains electrical supply in wall or ceiling at the mounting points.

Step 2: Feed cable coming from the rail, through the hole in the fix bases and then through hole in the wall/ceiling.

Step 3: Mount the 2x fix bases into the wall by first inserting the plastic expander and then screwing the ST5*45 mounting screw.

Step 4: Slide the ends of the rails over the fix bases and tighten the M5*6 mounting screws on the underside with allen key.

***NOTE: Any electrical work must be carried out by a qualified person only.**

